



The specifications below are for Megatex XD Screeners of standard construction, ranging from a single surface model (2 grades - 1 separation) to a 4 deck model (5 grades - 4 separations). Drawings are representative, but overall dimensions may vary depending on the mounting method.

### Examples of available Megatex™ XD Models

No. of Screen Surfaces	Number of Levels	Megatex Model No.	Normal Area per Surface		Motor		Principal Dimensions						Shipping Weight	
			ft²	m²	hp	kW	A		B		C		lb	kg
							in	mm	in	mm	in	mm		
1	3	3090-1†	90	8.4	15	11	86	2184	114	2896	246	6248	8600	3900
	4	4120-1†	120	11.2	15	11	94	2388	114	2896	246	6248	9500	4308
	5	5150-1	150	13.9	15	11	112	2845	114	2896	246	6248	10500	4762
	3	3180-1	180	16.7	15	11	106	2692	106	2692	252	6401	13200	5986
	6	6180-1†	180	16.7	15	11	Contact Rotex							
	4	4240-1	240	22.3	15	11	100	2540	180	4572	252	6401	12400	5624
	5	5300-1	300	27.9	15	11	106	2692	180	4572	265	6731	13600	6168
	6	6360-1	360	33.5	15/20**	11/15**	109	2769	180	4572	265	6731	15000	6803
	6	6360-1-S*	360	33.5	20	15	130	3302	180	4572	265	6731	17000	7710
	5	5430-1-S*	430	40.0	30	22	140	3556	212	5385	286	7264	23750	10771
8	8480-1	480	44.6	30	22	134	3404	180	4572	265	6731	20000	9070	
2	3	3090-2†	90	8.4	15	11	91	3211	117	2972	246	6248	9500	4308
	4	4120-2†	120	11.2	15	11	113	2870	130	3302	260	6604	10500	4762
	2	2120-2	120	11.2	15	11	100	2540	190	4826	252	6401	12600	5714
	5	5150-2†	150	13.9	15	11	118	2997	117	2972	246	6248	11900	5397
	3	3180-2	180	16.7	15	11	106	2692	190	4826	265	6731	13600	6168
	3	3180-2-S*	180	16.7	20	15	Contact Rotex							
	4	4240-2	240	22.3	20	15	117	2972	190	4826	265	6731	15500	7029
	5	5300-2	300	27.9	20	15	133	3378	190	4826	265	6731	18100	8209
	5	5430-2	430	40.0	30	22	134	3404	190	4826	294	7468	25600	11610
	3	3	3090-3†	90	8.4	15	11	112	2845	140	3556	260	6604	10500
2		2120-3	120	11.2	15	11	103	2616	210	5334	265	6731	13600	6168
2		2120-3-S*	120	11.2	20	15	119	3023	210	5334	252	6401	17100	7755
3		3180-3	180	16.7	15/20**	11/15**	117	2972	210	5334	265	6731	15500	7029
4		4240-3†	240	22.3	20	15	135	3429	210	5334	252	6401	19900	9025
4	2	2120-4†	120	11.2	15	11	108	2743	217	5512	217	5512	15800	7166
	3	3180-4†	180	16.7	20	15	129	3277	214	5436	220	5588	19000	8617

\* Indicates integral coarse scalp deck

\*\* Power requirement is volume/application specific (Contact Rotex).

† indicates single discharge door - "Half machine"

‡ indicates this model is available only with 4 degree decks. (Standard slope is 6 degrees.)

### Megatex™ XD Screeners vs. Conventional Screeners

Megatex XD Screeners have a unique stacked deck design within a compact machine. Several parallel fed surfaces do the job of multiple screeners, saving capital expense, floor space, energy and installation cost. At higher capacities increased screen width (16'-48'/4.0 m-14.6 m) is more effective than extended screen length because the bed depth is lower. Lower bed depth improves material stratification, so recovery efficiency and product accuracy are higher than competitive units.

➤ To find your local Rotex representative visit [www.rotex.com](http://www.rotex.com)